





## INDICATOREN / PANEELMETERS

	 Programmeerbaar met RFID / NFC Geen bedrading nodig!					
			<b>STR551</b>	<b>STR561</b>	<b>STR571</b>	<b>STR581</b>
Afmetingen (mm)			96 x 48 x 48	96 x 48 x 48	96 x 48 x 48	96 x 48 x 48
Voeding			24..230 V AC / DC 6 W - Isol. 2500 V	24..230 V AC / DC 6 W - Isol. 2500 V	24..230 V AC / DC 6 W - Isol. 2500 V	24..230 V AC / DC 6 W - Isol. 2500 V
Programmeerbare analoge-ingang			1	0	0	0
Strain Gauge analoge-ingang			0	1	0	0
Digitale-ingang			2	2	3	4
Relaisuitgang			2	2	2	2
Analoge-uitgang			●	● (0/4..20 mA)	○	2
RS485 / MODBUS			1	1	2	1
OLED display			●	●	●	●
Software toepassingen						
Teller / Telfrequentie						●
Som			●	●	○	○
Totalen			●	●	●	●
Auto kalibratie / tarra functie			○	●	○	○
Latch-On functie			●	○	●	○
Alarmen			2	2	2	4
Trend / staafdiagram			●	●	○	○
Datalogger			●	●	○	○
Analoge retransmission			●	●	○	○
Likiet controller (handreset)			●	●		○
Modbus master (8 variables)			○	○	●	○
Modbus multi-master			○	○	●	○
Easy-up codes			○	●	○	○
Geheugenkaart (USB)			●	●	●	●
Labsoftview (programming software)			●	○	○	○
"MyPixsys" NFC APP Android 			●	●	●	●
Applicaties						
Levensmiddelenindustrie			●	●	●	●
Koelapparatuur / HVAC			●	○	●	●
Verpakkingsindustrie			●	●	●	●
Plastic- en rubberindustrie			●	●	●	●
Laboratoriumapparatuur			●	●	○	○
Ovens / fornuizen			●	○	○	○
Branders / boilers			○	○	○	○
Modbus remote display			○	○	●	●
Productgroep			4800	4800	4800	4800
Artikelnummer			48001905	48003390	48003400	aanvraag