

							
	TCT101-1ABC	TCT101-2ABC	TCT101-3ABC	TCT101-4ABC-T	TCT201-1ABC	TCT201-2ABC	TCT201-3ABC
Afmetingen (mm)	32 x 74 x 53				48 x 48 x 107		
Voeding	24..230 V AC / DC 3 W - Isol. 2500 V				24..230 V AC / DC 3 W - Isol. 2500 V		
Digitale ingangen (NPN / PNP / TTL)	3	3	3	3	3	3	3
Relaisuitgang	2	2	2	1	2	2	2
Analoge ingang (potentiometer)	●	●	●	●	●	●	●
RS485 / MODBUS	○	○	○	●	○	○	○
Software toepassingen							
Timer (on-off / pauze-werk / oscillator / pwm)	●	○	○	●	●	○	○
Programmeerbare tijdbasis	●	○	○	●	●	○	○
Telmodus (up / down / lock / hold)	○	●	○	●	○	●	○
Telfrequentie (up to 100 KHz)	○	●	○	●	○	●	○
Tachometer (tot 100 KHz)	○	○	●	●	○	○	●
START / STOP / HOLD bij digitale ingang	●	●	●	●	●	●	●
Back-up batterij	●	●	●	●	●	●	●
Geheugenkaart	●	●	●	●	●	●	●
Labsoftview (programming software)	●	●	●	●	●	●	●
Encoder mono-directioneel (Push Pull / Line Driver)	○	●	●	●	○	●	●
Encoder Bi-directioneel (Push Pull / Line Driver)	○	●	●	●	○	●	●
Applicaties							
Levensmiddelenindustrie	●	●	●	●	●	●	●
Koelapparatuur / HVAC	○	○	○	○	○	○	○
Verpakkingsindustrie	●	●	●	●	●	●	●
Plastic- en rubberindustrie	●	●	●	●	●	●	●
Laboratoriumapparatuur	●	●	●	●	●	●	●
Ovens / fornuizen	●	●	●	●	●	●	●
Branders / boilers	●	●	●	●	●	●	●
Productgroep	4800	4800	4800	4800	4800	4800	4800
Artikelnummer	48003000	48003010	48003020	48003030	48003040	48003050	48003060