

TOSI 175

Cost-effective Plug & Go™ connectivity device

Tosi® 175 is ideal for demanding industry sectors that require an all-in-one solution that is compact, able to handle all environments and suited to global market usage. The 4G module and external 4G antenna provides stable Internet access, so the node can be easily configured anywhere. The versatile connectivity options, utilized in conjunction with leading edge Cyber security technology from Tosi enable diverse application scenarios. The durable aluminium alloy shell and small form factor allows for ideal mounting conditions. Creating secure and sustainable infrastructure has never been this easy.

The node is compatible with all existing Tosi® products.



Connect

Plug & Go™ deployment at any OT site - encrypted tunnels without network changes.



Visualize

Every gateway brings full OT site visibility to Tosi Control - one console, entire fleet.



Control

Built-in firewall, zero-trust, and AES-256 encryption - control who accesses what.

PERFORMANCE

- High VPN throughput, end-to-end encryption between Tosi devices, users and servers

INDUSTRIAL DESIGN

- Robust and fanless enclosure, DIN rail attachment

RELIABILITY

- Integrated WiFi as connectivity method or access point for wireless devices on site
- Built-in global LTE modem – no external modem needed
- TosiOnline automatic reconnection of dropped connections

TOSI 175 TECHNICAL DATA

Product code: **TBL175**

Certifications: CE, FCC, IMDA, RCM, MIC/JATE, WPC

PORTS

- 1 x RJ-45 WAN connection, 10/100 Mb/s, auto-negotiation (MDI / MDI-X)
- 1 x RJ-45 LAN connection, 10/100 Mb/s, auto-negotiation (MDI / MDI-X)
- LAN can be assigned as Service connection, 10/100 Mb/s, auto-negotiation (MDI / MDI-X)
- RS485 port is not supported in the software. The device can be powered through the port

CONNECTIONS

- 9-35V DC
- 2 x WiFi antenna connector, RP-SMA female
- 1 x LTE antenna connector, SMA female
- DIN rail attachment (back)
- Maximum power consumption 4W

CONNECTION FEATURES

- 3-way WAN priority
- Proxy server support
- WAN access with static addressing or DHCP
- Network Time Protocol (NTP) server
- Automatic LAN network discovery
- LAN access with mixed static addressing and DHCP server
- Management web UI access via http/https
- Modbus server
- Static routes
- Works in all Internet connections (operator independent)
- Works with dynamic, static and private IP addresses
- Built-in firewall, NAT
- Up to 10 concurrent VPN connections
- VPN throughput up to 10 Mbit/s
- TosiOnline™ automatic network recovery that recovers from most mobile operator and modem problems

4G MODULE

- Cellular module: Quectel EG25-G
- Region: Global
- LTE Cat-4
- Up to 150 Mbps DL, 50 Mbps UL

FREQUENCY BANDS

- LTE FDD: B1, B2, B3, B4, B5, B7, B8, B12, B13, B18, B19, B20, B25, B26, B28
- LTE TDD: B38, B39, B40, B41
- WCDMA: B1, B2, B4, B5, B6, B8, B19

WLAN

- IEEE 802.11 b/g, 2.4 GHz, max. 150 Mbps
- Encryptions WEP, WPA-PSK, WPA2-PSK, WPA-PSK/WPA2-PSK mixed mode
- Frequency 2.412 – 2.462 GHz, 11 channels
- Access point or client mode
- Output power 15 dBm max

PHYSICAL PROPERTIES

- Dimensions 104 mm x 28 mm x 110 mm / 4.09" x 1.10" x 4.33"
- Weight 305 g / 0.67 lbs (net weight article)

STORAGE TEMPERATURE

- Node -30°C ... +70°C / -22°F ... +158°F
- Power supply -20°C ... +80°C / -4°F ... +176°F

OPERATING TEMPERATURE


- Node -20°C ... +55°C / -4°F ... +131°F
- Power supply 0°C ... +40°C / 32°F ... +104°F

INCLUDED ACCESSORIES


- RJ-45 Cat5e Ethernet cable
- 1x LTE antenna
- 2x WiFi antenna
- DIN rail mount
- DC feed plug
- Wall mounting screw set
- Power supply unit
- AC adapter - Input 100 – 240 V AC, frequency 50/60Hz 0,3A, output 12.0 V, 1.0 A, max 12.0 W. EU, UK, AU and US power socket

Lights:

4G
Power
WiFi
WAN



LAN Ethernet port
WAN Ethernet port



Power port

Reset
(enable service port)

SIM holder



Safety Precaution

Do not use the provided power supply at temperatures exceeding 40 °C. To use the device in high temperatures, replace the power supply with a source rated for the used temperature.

US HQ
1212 Corporate Drive
Suite 170
Irving, Texas 75038

GLOBAL HQ
Elektroniikkatie 2a
7th floor
90590 Oulu, Finland

CONTACT US

in  **tosi**